

TECHNICAL DATA TENCATE ALL SEASON TOURING

The TenCate All Season Touring line of tent fabrics offers tent-manufacturers a choice of high-grade materials for every application, specifically for awnings. Within the Touring range, the WR-18 is ideally suited for roofing applications, and the WM-27 for walling applications.

Reference	Test method	WM-27	WR-18
Material		70/30 polyester/PVA	100% polyester
Coating		acrylic	acrylic
Width	ISO 22198	170 cm/205 cm/243 cm	164 cm/243 cm
Weight (+/- 5%)	ISO 3801	195 g/m ²	240 g/m ²
Tensile strength	ISO 13934-1		
Warp (5 cm)		110 daN	140 daN
Weft (5 cm)		100 daN	100 daN
Tearing strength	ISO 13937-1		
Warp (4,3 cm)		2,0 daN	2,0 daN
Weft (4,3 cm)		1,5 daN	1,5 daN
Dimensional change in wet condition	NFG 07-052		
Warp		< - 1 %	< - 1 %
Weft		0 %	0 %
Watercolumn*	ISO 811	≥ 60 cm	≥ 85 cm
Colour-weather fastness	ISO 105 B04	≥6	≥6 (coated side)

Please note that if you combine materials, such as ground sheet, mud skirts, windows, zips, etc., these products may have an adverse effect on each other. This is your own responsibility and we therefore advise you to carry out extensive tests beforehand.